

Technical Specifications







Table of Contents

- 4 Product Options
- 5 Ordering
- 6 Performance Rating Information and Standards
- 7 Modern Awning/Modern Casement
- 10 Modern Casement/Modern Casement Push Out
- 11 Modern Automated Awning/Casement
- 12 Modern Direct Glaze
- 17 Modern Inswing/Outswing Door
- 21 Modern Sliding Door
- 23 Modern Multi-Slide Door


DIRECT GLAZE WINDOWS
Bronze

Product Options


Divided Lites




2 7/8" SDL
15/16" Dual Pane




1 1/8" SDL
15/16" Dual Pane




7/8" SDL
15/16" Dual Pane




2 7/8" SDL
1 1/4" Tripane




1 1/8" SDL
1 1/4" Tripane




7/8" SDL
1 1/4" Tripane



2 7/8" SDL
1 9/16" Tripane



1 1/8" SDL
1 9/16" Tripane



7/8" SDL
1 9/16" Tripane

* The 1 9/16" tripane is only available with Modern Direct Glaze.

Ordering

The following pages include specifications for many of the standard windows and doors Marvin manufactures. For complete specification information, visit marvin.com or contact your local Marvin representative. There's a lot of information here, but once you understand the different elements, these pages will become the first step in seeing your window and door dreams become a reality. So when you meet with your local Marvin representative, you'll be speaking the same language. And should you have something special in mind, remember that in addition to the thousands of standard offerings listed here, our favorite challenge is creating a custom window or door that has never been built before.

Operating vs. Stationary

Marvin drawings always illustrate the window sash or door panels as if you are looking from the outside in. Identifying which sash or panels are operating is a little counter-intuitive. X means operating, O means stationary. So when listing the sash or panels, start from the left to right looking from the exterior. For example, a two panel French door with a left operating panel and a right stationary panel would be identified as XO. A French door with two operating panels would be identified as XX.

The identification of stationary/operating panels is then followed by the handing of the primary operating panel (the one that would be opened first, in the case of two operating panels). If you stand straddling the sill of a door with your back to the hinge of the operating panel, notice which hand you would use to reach out and close the door. That indicates whether a door panel is "R" - right handing or "L" - left handing for Marvin residential doors.



Ordering Considerations

All products are ordered through window and door professionals. They'll take care of you every step of the way, working with you to specify each detail. Since Marvin products are not warehoused and are made to order to your exact needs, product returns are at the discretion of your individual dealer.

Listed below are some of the details you may want to consider:

- Glazing options such as insulating glass and Low E3 to optimize energy efficiency
- Divided Lite options: Simulated Divided Lite with spacers, Simulated Divided Frame
- Hardware finishes
- Sill types
- Operating vs. stationary sash and panels
- Screen needs
- Jamb depth needs
- Performance needs
- Automation needs

All performance information is based on Marvin installation recommendations for standard products. Please consult your local Marvin representative for more information. For further details and drawings visit the 'Technical Specifications' section at marvin.com.

The information provided in this catalog has been gathered and assembled with every effort made to validate accuracy and consistency of the content. However, Marvin does not make any warranty or guarantee as to this information. Please verify critical product data in Marvin Order Management System (OMS) quotes and at the time of ordering.

Performance Rating Information and Standards

As you flip through this catalog, you'll see different ratings on the performance of Marvin windows and doors. Here's some brief background information:

WDMA Standards

The Window and Door Manufacturers Association (WDMA) in conjunction with other organizations in the industry developed standards that make it easy to compare windows and doors from different manufacturers, testing product performance regarding air and water infiltration, as well as physical loads on the exterior and interior (very important when you consider the pressure differentials that can occur in coastal areas, as well as forced entry resistance). Marvin products are rated in accordance with the AAMA/WDMA/CSA 101/I.S.2/A440. Standards are certified in compliance with the WDMA Hallmark program.

Performance Grade (PG)

A Performance Grade (PG) rating is given to products that comply with and attain a specific level of performance in accordance with current testing standards/specifications created by AAMA/WDMA/CSA standards. Once all applicable testing has been successfully completed for air infiltration, water penetration resistance, and structural loading which also includes load deflection, ease of operation, and forced entry resistance testing, a PG rating is given. The higher a PG number the product is rated, the better the performance.

NFRC

Marvin is a member of the National Fenestration Rating Council, an independent, non-profit organization that has established an energy performance rating system for accurately comparing different window and door products. Some factors considered in creating an individual window or door's rating include: the U-factor (measuring heat loss), the solar heat gain coefficient, and visible light transmission, evaluating the frame, sash and glass in its entirety.

ENERGY STAR®

The U.S. Department of Energy and the U.S. Environmental Protection Agency created this standard to help consumers identify products that reduce energy use. Windows and doors that qualify for ENERGY STAR are much more efficient as an average window produced ten years ago and must be rated, certified, and labeled according to the NFRC. To get current energy data, go to energystar.gov.

Egress Code

International Building Code – 2012 and 2015 Section 1009 Emergency Escape and Rescue.

1026.2 Minimum size: Emergency escape and rescue openings shall have a minimum net clear opening of 5.7 sq ft (0.53 m2). Exception: The minimum net clear opening for emergency escape and rescue openings on the ground level at grade is 5.0 sq ft (0.46 m2).

1026.2.1 Minimum dimensions: The minimum net clear opening height dimension shall be 24 inches (610 mm). The net clear opening width dimension shall be 20 inches (508 mm). The net clear opening dimensions shall be the result of normal operation of the opening.

1026.3 Maximum height from the floor: Emergency escape and rescue opening shall have the bottom of the clear opening not greater than 44 inches (1118 mm) measured from the floor.

1026.4 Operational constraints: Emergency escape and rescue openings shall be operational from the inside of the room without the use of keys or tools. Bars, grilles, grates or similar devices are permitted to be placed over emergency escape and rescue openings provided the minimum net clear opening size complies with Section 1026.2 and such devices shall be releasable or removable from the inside without the use of a key, tool or force greater than that which is required for normal operation of the escape and rescue opening. Where such bars, grilles, grates or similar devices are installed in existing buildings, smoke alarms shall be installed in accordance with section 907.2.10 regardless of the valuation of the alteration.

Code restrictions may vary depending on your local building codes.

Modern Awning / Modern Casement

Certified Sizes

Product	Air Tested to PSF	Water Tested to PSF	Design Pressure (DP)	Certification Rating	Max Overall Width		Max Overall Height	
					in	mm	in	mm
MCA, MCAPO, MCAMOTO	1.57	12.1	50	CW-PG50-C	32	(813)	108	(2743)
MCA, MCAPO, MCAMOTO	1.57	12.1	50	CW-PG50-C	36	(914)	102	(2591)
MCA, MCAPO, MCAMOTO	1.57	12.1	50	CW-PG50-C	40	(1016)	96	(2438)
MCA, MCAPO, MCAMOTO	1.57	12.1	50	CW-PG50-C	44	(1118)	92	(2337)
MAWN	1.57	12.1	50	CW-PG50-C	64	(1626)	96	(2438)
MAWN	1.57	12.1	45	LC-PG45-C	96	(2438)	64	(1626)
MAWN	1.57	12.1	50	CW-PG50-C	72	(1829)	72	(1829)
MAWNPO	1.57	12.1	50	CW-PG50-C	89	(2261)	48	(1219)
MAWNMOTO	1.57	12.1	50	CW-PG50-C	96	(2438)	40	(1016)
MAWNMOTO	1.57	12.1	50	CW-PG50-C	92	(2337)	44	(1118)
MCAP	1.57	12.1	50	CW-PG50-FW	108	(2743)	74	(1880)
MCAP	1.57	12.1	50	CW-PG50-FW	74	(1880)	108	(2743)
MCAP	1.57	12.1	50	CW-PG50-FW	102	(2591)	79	(2007)
MCAP	1.57	12.1	50	CW-PG50-FW	79	(2007)	102	(2591)
MCAP	1.57	12.1	50	CW-PG50-FW	96	(2438)	84	(2134)
MCAP	1.57	12.1	50	CW-PG50-FW	84	(2134)	96	(2438)
* **Casement Mull (all products)	1.57	7.5	40	CW-PG40-FW	168	(4267)	96	(2438)
* **Casement Mull (all products)	1.57	7.5	40	CW-PG40-FW	96	(2438)	168	(4267)

MODERN PRODUCTS ARE AVAILABLE TO 1/32 OF AN INCH.

Abbreviations

MAWN: MODERN AWNING

MAWNPO: MODERN AWNING PUSH OUT

MAWNMOTO: MODERN AWNING MOTORIZED

MCA: MODERN CASEMENT

MCAPO: MODERN CASEMENT PUSH OUT

MCAMOTO: MODERN CASEMENT MOTORIZED

MCAP: MODERN CASEMENT PICTURE UNIT

Modern Awning / Modern Casement

Egress Chart

Modern Automated Awning						
	Frame width (inches)	23.500	72.000	72.001	92.000	92.001
Frame Height (inches)	Max sash opening angle					
18.000	27 degrees					
19.999						
20.000						
23.999	36 degrees					
24.000						
29.749						
29.750	25 degrees					
35.999						
36.000						
40.000	23 degrees					
40.001						
44.000						

Non-Certified Sizes
Custodial Sash Limiter Required


Modern Automated Casement																
	Frame width (inches)	20.000	26.999	27.000	28.000	29.749	29.750	30.000	32.000	34.000	34.999	35.000	36.000	38.000	40.000	42.000
Frame Height (inches)	Max Sash Opening Angle	54 degrees		75 degrees			69 degrees						55 degrees			
23.500																
37.999				38" is the minimum frame height for egress*												
38.000																
40.000																
42.000																
44.000																
46.000																
72.000																
72.001																
92.000																
92.001																
96.000																
96.001																
102.000																
102.001																
108.000																

Custodial Sash Limiter Required


* 38" is the minimum frame height to use the manual capable lock actuator needed for manual egress

Modern Awning / Modern Awning Push Out


Construction Details




HEAD JAMB AND SILL - CRANK OUT OPERATOR




HEAD JAMB AND SILL - PUSH OUT OPERATOR, STATIONARY




JAMB - CRANK OUT OPERATOR




JAMB - PUSH OUT OPERATOR STATIONARY




HORIZONTAL MULL - CRANK OUT OPERATOR



VERTICAL MULL - CRANK OUT OPERATOR




HORIZONTAL MULL - PUSH OUT OPERATOR, STATIONARY




VERTICAL MULL - PUSH OUT OPERATOR, STATIONARY

Modern Casement / Modern Casement Push Out

Construction Details




CASEMENT STANDARD OPERATION AS VIEWED FROM THE OUTSIDE



Modern Automated Awning / Casement

Construction Details



Please consult your local Marvin representative for more information.
For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Modern Direct Glaze

Certified Sizes and Ratings


Commercial Rating									
Product	Air Tested to PSF	Water Tested to psf	Structural Tested psf	Performance Grade (PG)	Certification Rating	Max Overall Width		Max Overall Height	
						in	mm	in	mm
Direct Glaze Unit	6.24	12.1	60.0	40	CW-PG40-FW	141 3/8	(3591)	93 3/8	(2372)
Direct Glaze Unit	6.24	12.1	60.0	40	CW-PG40-FW	93 3/8	(2372)	141 3/8	(3591)
Direct Glaze Unit	6.24	12.1	90.0	60	CW-PG60-FW	141 3/8	(3591)	93 3/8	(2372)
Direct Glaze Unit	6.24	12.1	90.0	60	CW-PG60-FW	93 3/8	(2372)	141 3/8	(3591)
*Direct Glaze Assembly	1.57	7.5	60.0	40	CW-PG40-FW	168	(4267)	96	(2438)
*Direct Glaze Assembly	1.57	7.5	60.0	40	CW-PG40-FW	96	(2438)	168	(4267)
**Direct Glaze Unit	6.24	12.1	60.0	40	CW-PG40-FW	121 3/8	(3083)	62 9/16	(1589)
**Direct Glaze Unit	6.24	12.1	60.0	40	CW-PG40-FW	62 9/16	(1589)	121 3/8	(3083)
**Direct Glaze Unit	6.24	12.1	90.0	60	CW-PG60-FW	121 3/8	(3083)	62 9/16	(1589)
**Direct Glaze Unit	6.24	12.1	90.0	60	CW-PG60-FW	62 9/16	(1589)	121 3/8	(3083)
***Direct Glaze Corner Unit	6.24	12.1	60.0	40	CW-PG40-FW	93 3/8	(2372)	141 3/8	(3591)

* 84" maximum tributary span
** Largest size with annealed glass
*** Max overall width is for each direct glaze frame om is 93 3/8". Including the corner post, the unit om width would be 94 13/16".
Note: Certification based upon AAMA/WDMA/CSA 101/i.S.2/a440-08.
Corner units are rectangular only.

Modern Direct Glaze Polygon Shapes


How to Specify Dimensions

When ordering a trapezoid, triangle, or rectangle window, provide a sketch of the unit as viewed from the exterior, plus include key rough opening dimensions. Example: To order a window of a trapezoid opening, provide the measurements of each side. For other shapes, provide all known dimensions.




Modern Direct Glaze Rectangle


Construction Details



DIRECT GLAZE RECTANGLE
HEAD JAMB AND SILL WITH
1 1/4" DUAL PANE




DIRECT GLAZE RECTANGLE
JAMB WITH
1 1/4" DUAL PANE




HORIZONTAL MULLION

VERTICAL MULLION



DIRECT GLAZE RECTANGLE
HEAD JAMB AND SILL WITH
1 9/16" TRIPLE PANE



DIRECT GLAZE RECTANGLE
JAMB WITH
1 9/16" TRIPLE PANE




HORIZONTAL MULLION


VERTICAL MULLION

Modern Direct Glaze Polygon


Construction details



DIRECT GLAZE POLYGON
HEAD JAMB AND SILL WITH
1 1/4" DUAL PANE




DIRECT GLAZE POLYGON
JAMB WITH
1 1/4" DUAL PANE




HORIZONTAL MULLION

VERTICAL MULLION



DIRECT GLAZE POLYGON
HEAD JAMB AND SILL WITH
1 9/16" TRIPLE PANE



DIRECT GLAZE POLYGON
JAMB WITH
1 9/16" TRIPLE PANE




HORIZONTAL MULLION

VERTICAL MULLION

Please consult your local Marvin representative for more information.
For further details and drawings visit the 'Technical Specifications' section at marvin.com.

Modern Direct Glaze Corner Units

Construction details



Please consult your local Marvin representative for masonry openings that include casings and subsills.
For further details and drawings visit the 'Technical Specifications' section at marvin.com.

Modern Inswing / Outswing Door

Certified sizes and ratings


Modern Inswing Door										
Certification based on AAMA/WDMA/CSA 101/I.S.2/A440										
Product	# of Panels	Sill Type	Air Tested to psf	Water Tested to psf	Structural Tested to psf	Performance Grade	Design Pressure	Overall Width	Overall Height	Applicable Configurations
Modern Inswing Door (O)	1	Performance Sill	6.24	6	+ 60 - 60	CW-PG40-FD	+ 40 - 40	99.246	148.018	O
Modern Inswing Door (O)	1	Low Profile Sill	6.24	4.5	+ 52.5 - 52.5	CW-PG30-FD	+ 35 - 35	99.246	148.018	O
Modern Inswing Door (O)	1	Performance Sill	6.24	6	+ 60 - 60	CW-PG40-FD	+ 40 - 40	147.246	100.018	O
Modern Inswing Door (O)	1	Low Profile Sill	6.24	4.5	+ 52.5 - 52.5	CW-PG30-FD	+ 35 - 35	147.246	100.018	O
Modern Inswing Door (XO/OX) Jamb Hinged	2	Performance Sill	6.24	6	+ 60 - 60	LC-PG40-SHD	+ 40 - 40	96	120	X, O, XO, OX
Modern Inswing Door (XO/OX) Jamb Hinged	2	Low Profile Sill	6.24	4.5	+ 45 - 45	LC-PG30-SHD	+ 30 - 30	96	120	X, O, XO, OX
Modern Inswing Door (XX) Jamb Hinged	2	Performance Sill	6.24	6	+ 60 - 60	LC-PG40-SHD	+ 40 - 40	96	120	X, XX
Modern Inswing Door (XX) Jamb Hinged	2	Low Profile Sill	6.24	4.5	+ 45 - 45	LC-PG30-SHD	+ 30 - 30	96	120	X, XX

Modern Outswing Door										
Certification based on AAMA/WDMA/CSA 101/I.S.2/A440										
Product	# of Panels	Sill Type	Air Tested to psf	Water Tested to psf	Structural Tested to psf	Performance Grade	Design Pressure	Overall Width	Overall Height	Applicable Configurations
Modern Outswing Door (O)	1	Performance Sill	6.24	6	+ 60 - 60	CW-PG40-FD	+ 40 - 40	99.246	148.018	O
Modern Outswing Door (O)	1	Low Profile Sill	6.24	4.5	+ 45 - 45	CW-PG30-FD	+ 30 - 30	99.246	148.018	O
Modern Outswing Door (O)	1	Performance Sill	6.24	6	+ 60 - 60	CW-PG40-FD	+ 40 - 40	147.246	100.018	O
Modern Outswing Door (O)	1	Low Profile Sill	6.24	4.5	+ 45 - 45	CW-PG30-FD	+ 30 - 30	147.246	100.018	O
Modern Outswing Door (XO/OX) Jamb Hinged	2	Performance Sill	6.24	6	+ 60 - 60	LC-PG40-SHD	+ 40 - 40	96	120	X, O, XO, OX
Modern Outswing Door (XO/OX) Jamb Hinged	2	Low Profile Sill	6.24	4.5	+ 45 - 45	LC-PG30-SHD	+ 30 - 30	96	120	X, O, XO, OX
Modern Outswing Door (XX) Jamb Hinged	2	Performance Sill	6.24	6	+ 60 - 60	LC-PG40-SHD	+ 40 - 40	96	120	X, XX
Modern Outswing Door (XX) Jamb Hinged	2	Low Profile Sill	6.24	4.5	+ 45 - 45	LC-PG30-SHD	+ 30 - 30	96	120	X, XX


MODERN INSWING DOOR: MID
MODERN OUTSWING DOOR: MOD

Modern Inswing / Outswing Operating Configurations

INSWING DOOR CONFIGURATIONS



OUTSWING DOOR CONFIGURATIONS





O: STATIONARY X: OPERATING L: LEFT HAND R: RIGHT HAND
Please consult your local Marvin representative for more information.
For further details and drawings visit the 'Technical Specifications' section at [marvin.com](https://www.marvin.com).


MODERN INSWING DOOR: MID
MODERN OUTSWING DOOR: MOD

Modern Inswing Door


Construction details




LOW PROFILE SILL




SADDLE SILL




HORIZONTAL MULLION




VERTICAL MULLION




O JAMB



X R JAMB WITH RH SCREEN




2 PANEL JAMB OX LH WITH RH SCREEN




2 PANEL JAMB XX RH WITH SCREEN

Modern Outswing Door


Construction details




4 9/16" HEAD JAMB AND SILL WITH PERFORMANCE SILL




O JAMB




X L JAMB WITH RH SCREEN




LOW PROFILE SILL




SADDLE SILL




HORIZONTAL MULLION



VERTICAL MULLION



2 PANEL OX JAMB OX WITH SCREEN




2 PANEL XX JAMB WITH SCREEN

Modern Sliding Door

Certified sizes and ratings and configurations

Product	Air Tested to psf	Water Tested to psf	Design Pressure (DP)	Certification Rating	Overall Width		Overall Height	
					in	mm	in	mm
Sliding Door (O)	1.57	6	40	LC-PG40-SD	63	(1600)	122 29/32	(3122)
Sliding Door (XO/OX)	1.57	6	40	LC-PG40-SD	120 3/32	(3050)	122 29/32	(3122)
Sliding Door (XOO/OOX)	1.57	6	40	LC-PG40-SD	181 1/16	(4599)	122 29/32	(3122)
Sliding Door (O-XO/OX-O)	1.57	6	40	LC-PG40-SD	181 1/16	(4599)	122 29/32	(3122)
Sliding Door (OX-XO)	1.57	6	40	LC-PG40-SD	238 3/16	(6050)	122 29/32	(3122)


CONFIGURATIONS



MODERN SLIDING DOOR: MSD

Modern Sliding Door


Construction details




Please consult your local Marvin representative for more information.
For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Modern Multi-Slide Door

Configurations - Uni-Directional Stacked



OPTIONAL SILLS - STACKED AND POCKET UNITS




MODERN MULTI-SLIDE DOOR POCKET: MSD PKT
MODERN MULTI-SLIDE DOOR STACKED: MSD STK


Modern Multi-Slide Door

Configurations - Bi Parting and Center Stacked

BI-PARTING




CENTER STACKED



Please consult your local Marvin representative for more information.
For further details and drawings visit the 'Technical Specifications' section at [marvin.com](https://www.marvin.com).

Modern Multi-Slide Door


Configurations - Uni-Directional Pocket



Please consult your local Marvin representative for more information.
For further details and drawings visit the 'Technical Specifications' section at [marvin.com](https://www.marvin.com).


Modern Multi-Slide Door

Configurations - Bi Parting Pocket




Modern Multi-Slide Door

Construction Details - Uni-Directional and Bi Parting Stacked




Modern Multi-Slide Door

Construction Details - Uni-Directional and Bi Parting Pocket



Modern Multi-Slide Door Screens

Construction Details - Uni-Directional and Center Stacked





CASEMENT,
AWNING WINDOWS
Ebony



Since 1912, Marvin has been a family-owned and -led company, with a legacy of innovation and commitment to the highest quality. We understand the unique opportunity windows and doors have to improve our spaces and how we feel in them. That's why we never stop pushing what's possible and inventing new solutions to channel fresh air, enhance light quality, and connect with the world around us.

MARVIN.COM

© 2026 Marvin Lumber and Cedar Co., LLC. All rights reserved.
® Registered trademark of Marvin Lumber and Cedar Co., LLC.

Information regarding status of patent applications, as well as product features and specifications, is subject to change without notice.

Part 19983466. January 2026.

Colors shown in printed materials are simulations and may not precisely duplicate product or finish colors. Contact your local Marvin dealer to view actual product and finish color samples.