

## Declaration of Design and Performance

**DDP No.:** 120-00003

**Issue No.:** 3.1

**Approving authority:** n/a

**DDP Change Control Ref:** JIRA No. HWD-424

*Note: Before specifying equipment, check with Flightcell International that this declaration is the currently valid version*

### MANUFACTURER

Flightcell International Ltd

Address: 98 Vickerman St, Nelson, New Zealand 7010

### DECLARATION OF DESIGN AND PERFORMANCE

**System Name:** Flightcell DZMx Plus

**Part No.:** DZP\_07-XXX-XXXX (-XXX-XXXX represents the dash number which defines the specific configuration of the unit, the detailed breakdown of the dash number is contained in 113-00002 Rev 2.0 DZP\_07 Flightcell DZMx Plus Dash Number Definition Table).

Description: Avionics bay mounted, all-in-one Iridium and cellular solution for global voice, data, and GPS tracking. It is a straight LRU swap-out for ageing tray mounted satcom tracking systems.

Data interfaces include Ethernet, USB, Wi-Fi, Bluetooth, ARINC 429, Software Defined Receiver, Cellular Modem, Iridium Modem, General Purpose Inputs and General-Purpose Outputs. The product is designed for standard ARINC 600 2 MCU avionics bay rack.

**Rev No.:** 4.0

**Weight & Overall Dimensions:** Representative configurations range from 1600g maximum. For specific information refer to 100-00006 Rev 4.0 DZP\_07 Master Data List.

System Wiring Diagrams	
Diagram No.	Description
114-00018	DZMx Plus Interconnect Drawings

<b>Overall Dimensions</b> <i>for more specific data, refer to the assembly diagrams and definition specification below</i>	
<b>Part Description</b>	<b>DZMx Plus</b>
Weight	1.6kg (depending on configuration)
Length	240mm
Width	58mm
Height	188mm

#### Performance:

The Flightcell DZMx Plus meets all the specifications and requirements as outlined in this document. The main performance specifications are listed below.

Item	Detail
Interface	10/100 Ethernet, USB 2.0, RS-485, RS-232, Analog audio (2), GPI (5), GPO (2), Wi-Fi, Bluetooth Optional extras: GPI(7), ARINC 429
DC Power Source	+12V - +32VDC (28V nominal) Max current: ~1.5A @ 28VDC
Connectors	Main connector: D-SUB 62 HD male, mating connector: M24308/2-14F

Wi-Fi / Bluetooth Transceiver transmit power (if installed)		
Modem	Description	RF Performance
Wi-Fi	Tx power (dBm)	16
	Antenna gain (dBi)	2.0
	Total power (dBm)	18
	Total power (mW)	63.1
Bluetooth	Tx power (dBm)	10.0
	Antenna gain (dBi)	2.0
	Total power (dBm)	12.0
	Total power (mW)	15.9

Cellular / Satellite Transceiver transmit power (if installed)	
Cell (WP76XX Series/MPL200)	TX Power
<b>LTE (4G)</b> As per 3GPP TS 36.521-1 Power Class 3	+23dBm +/-2dB
<b>UMTS/HSDPA/HSUPA (3G)</b> As per 3GPP TS 34.121-1 Power Class 3	+24dBm +1/-3dB
<b>GSM/GPRS (2G)</b> As per 3GPP TS 51.010-1	

Cellular / Satellite Transceiver transmit power (if installed)	
Cell (WP76XX Series/MPL200)	TX Power
GMSK Power Class 4 for GSM/E-GSM bands	+33dBm +/-2.5dB
GMSK Power Class 1 for DCS/PCS bands	+30dBm +/-2.5dBm
EDGE (2G) As per 3GPP TS 51.010-1	
8-PSK Power Class E2 for GSM/E-GSM bands	+27dBm +/-3dB
8-PSK Power Class E2 for DCS/PCS bands	+26dBm +/-4dBm
Iridium 9523N	TX Power
Average power during a transmit slot (max)	7W
Average Power during a frame (typical)	0.6W
Iridium 9603N	TX Power
Average power during a transmit slot (max)	1.6W

Software Defined Receiver	
	RX Power
RX Power	-5dBm +/-1dB
RX Power (RX amplifier disabled)	+10dBm +/-1dB
Operating frequency	1 MHz to 2 GHz

**Test Report References:** HSVCR91380\_FlightCell\_DO160\_Vibration\_RevA, FINAL FinalCell45076-signed, 105415-9\_Final\_UP(1), 106565-3\_Final, 109461-9\_Final\_UP

**Fault analysis reports:** n/a

**Installation and Operation References:**

Manual No.	Description
117-00010	DZMx Plus Installation Manual
117-00009	DZMx / DZMx Plus Operator Manual

**Declarations:**

The limits of declared performance and those implied by the declarations below are not intended to be absolute, but are intended to indicate performance which has been shown by tests.

**Cooling Requirements**

The unit is passively cooled. No special cooling required.

**Ingress of fluids, sand and dust**

The unit is designed to be protected against fluids, sand and dust to a rating of IP54, however no external testing has been completed.

A rating of IP54 means that the unit is protected against ingress of dust in sufficient quantities to interfere with satisfactory operation of the unit and against harmful ingress of water when subjected to water splashing against the enclosure from any direction).

**Storage**

The unit should be stored at a temperature of not less than -55°C and not more than +85°C.

**Ambient Operating temperature**

The ambient operating temperature range for the unit is -20°C to +55°C.

**Storage Life**

The shelf storage life is not less than 5 years under controlled storage conditions.

**CERTIFICATION**

The declaration in this document is made under the authority of Flightcell International Ltd.

Flightcell International Ltd cannot accept responsibility for equipment used outside the limiting conditions stated above without their agreement.

Signed: \_\_\_\_\_

Authorised Signature: John Wyllie  
Position: Accountable Manager  
Effective Date: 7 April 2025

**REMARKS****Nameplate Marking:** DO-160G Env. Cat. [(A1)(B1)(F1)]BAB[UG]HXXXXZZAZ[AC][SS]MXXXXXXAX

CONDITIONS	DO-160G Section#	Description of Tests
Temperature & Altitude	4.0	Equipment tested to categories A1, B1, F1  No Forced cooling required  Equipment identified as category X, no test performed.
Low Temperature	4.5.1	
High Temperature	4.5.2 & 4.5.3	
In-Flight Loss of Cooling	4.5.4	
Altitude	4.6.1	
Decompression	4.6.2	
Overpressure	4.6.3	
Temperature Variation	5.0	Equipment tested to category B.
Humidity	6.0	Equipment tested to category A.
Operational Shocks	7.2	Equipment tested to category B, aircraft type 5, test type 5. (DZP_07-X0X-XXXX variant not tested, category X) Equipment tested to category B, aircraft type 5, test type 5. (DZP_07-X0X-XXXX variant not tested, category X)
Crash Safety	7.3	
Vibration	8.0	Equipment identified as category U, Aircraft zone 2, Test Curve G. (DZP_07-X0X-XXXX variant not tested, category X)
Explosive Atmosphere	9.0	Equipment tested to category H.
Waterproofness	10.0	Equipment identified as category X, no test performed.
Fluids Susceptibility	11.0	Equipment identified as category X, no test performed.
Sand and Dust	12.0	Equipment identified as category X, no test performed.
Fungus	13.0	Equipment identified as category X, no test performed.
Salt Fog	14.0	Equipment identified as category X, no test performed.
Magnetic Effect	15.0	Equipment tested to category Z.
Power Input	16.0	Equipment tested to category Z.
Voltage Spike	17.0	Equipment tested to category A.
Audio Frequency Susceptibility	18.0	Equipment tested to category Z.
Induced Signal Susceptibility	19.0	Equipment tested to category AC.
Radio Frequency Susceptibility	20.0	Equipment tested to category S.
Radio Frequency Emissions	21.0	Equipment tested to category M.
Lightning Induced Transient Effects	22.0	Equipment identified as category X, no test performed.
Lightning Direct Effects	23.0	Equipment identified as category X, no test performed.
Icing	24.0	Equipment identified as category X, no test performed.
Electrostatic Discharge	25.0	Equipment tested to category A.
Fire, Flammability	26.0	Equipment identified as category X, no test performed.
Other Tests		

*Except as expressly provided below, no part of this document may be reproduced, copied, transmitted, disseminated, downloaded, or stored in any storage medium, for any purpose other than that which Flightcell International has provided this document for. Any electronic or printed copy of this document or any revision must contain the complete text of this copyright notice. Any unauthorised commercial distribution of this document or any revision hereto is strictly prohibited. Information in this document is subject to change. Document users are responsible for ensuring printed copies are valid prior to use.*

© Copyright 2025 Flightcell International Ltd – All Rights Reserved