

-10%

815 Series, ASME Class 150, Bare Shaft High-Performance Butterfly Valves (2-1/2" – 12")

Materials				Figure Number	Size (in.)							
Body	Disc	Shaft	Seats		2 1/2	3	4	5	6	8	10	12
Wafer Style Body												
Carbon Steel	316SS	316SS	PTFE	815W 11 2236TT	875	897	1,093	1,751	1,791	2,364	4,288	5,717
		17-4PH	PTFE	815W 11 22HBTT								
		316SS	Xtreme	815W 11 2236XZ	929	961	1,187	1,845	1,893	2,518	4,430	5,776
		17-4PH	Xtreme	815W 11 22HBXZ								
316 SS	316SS	316SS	PTFE	815W 11 3600TT	1,329	1,373	1,659	2,464	2,573	3,530	6,046	7,658
		17-4PH	PTFE	815W 11 36HBTT								
		316SS	Xtreme	815W 11 3600XZ	1,381	1,426	1,736	2,537	2,621	3,622	6,125	8,037
		17-4PH	Xtreme	815W 11 36HBXZ								
Lugged Style Body												
Carbon Steel	316SS	316SS	PTFE	815L 11 2236TT	1359	1410	1687	2510	2642	3370	5069	6553
		17-4PH	PTFE	815L 11 22HBTT								
		316SS	Xtreme	815L 11 2236XZ	1407	1438	1736	2612	2694	3453	5230	6694
		17-4PH	Xtreme	815L 11 22HBXZ								
316 SS	316SS	316SS	PTFE	815L 11 3600TT	1906	1982	2416	3878	4069	5138	7482	10035
		17-4PH	PTFE	815L 11 36HBTT								
		316SS	Xtreme	815L 11 3600XZ	1964	2033	2515	3977	4095	5242	7638	10160
		17-4PH	Xtreme	815L 11 36HBXZ								
Carbon Steel	Monel	Monel	Xtreme	815LC 11 2271XZ	NA	2,382	2,816	NA	4,060	5,452	8,181	10,661

Note: CE marked products (per the European Pressure Equipment Directive) are available at no additional charge. See Product bulletin for proper code.

Butterfly Valves (14" – 60")

Materials				Figure Number	Size (in.)							
Body	Disc	Shaft	Seats		14	16	18	20	24	30	36	42 - 60
Wafer Style Body												
Carbon Steel	316SS	17-4PH	Xtreme	815W 11 22HBXZ	7,592	10,992	13,227	16,503	23,713	54,059	NA	NA
316SS		316SS		815W 11 3600XZ	12,609	15,735	20,893	25,591	35,619	64,406		
Lugged Style Body												
Carbon Steel	316SS	17-4PH	Xtreme	815L 11 22HBXZ	8,162	12,755	14,900	18,830	27,084	65,720	90,662	OA
Monel	Monel	815LC 11 2271XZ		13,720	19,042	23,493	31,191	42,712	OA			
316SS	316SS	316SS		815L 11 3600XZ	13,304	16,686	22,098	28,455	42,056	77,403	108,286	

Note: CE marked products (per the European Pressure Equipment Directive) are available at no additional charge. See Product bulletin for proper code.

F815 Series, ASME Class 150 Fire-Tite® High-Performance Butterfly Valves (3" – 12")

Materials				Figure Number	Size (in.)					
Body	Disc	Shaft	Seats		3	4	6	8	10	12
Wafer Style Body										
Carbon Steel	316SS	316SS	PTFE & 316SS	F815W 31 2236AE	1,210	1,471	2,061	2,879	4,797	6,240
		17-4PH		F815W 31 22HBAE						
316SS	316SS	316SS		F815W 31 3600AE	1,500	1,935	2,816	3,892	6,592	8,647
		17-4PH		F815W 31 36HBAE						
Lugged Body Style										
Carbon Steel	316SS	316SS	PTFE & 316SS	F815L 31 2236AE	1,616	1,935	2,929	3,752	5,683	7,273
		17-4PH		F815L 31 22HBAE						
316SS	316SS	316SS		F815L 31 3600AE	2,175	2,667	4,451	5,693	8,298	11,041
		17-4PH		F815L 31 36HBAE						

Note: CE marked products (per the European Pressure Equipment Directive) are available at no additional charge. See Product bulletin for proper code.

Hi-Performance Butterfly Valves (14" – 24")

Materials				Figure Number	Size (in.)				
Body	Disc	Shaft	Seats		14	16	18	20	24
Wafer Style Body									
Carbon Steel	316SS	17-4PH	PTFE & 316SS	F815W 31 22HBAE	10,548	14,681	17,636	21,627	30,614
316SS				F815W 31 36HBAE	OA				
Lugged Style Body									
Carbon Steel	316SS	17-4PH	PTFE & 316SS	F815L 31 22HBAE	11,224	16,328	19,640	24,327	34,684
316SS				F815L 31 36HBAE	OA				

Note: CE marked products (per the European Pressure Equipment Directive) are available at no additional charge. See Product bulletin for proper code.