

Product Description

Kingspan Metal Batten Strip is an 18-gauge steel strip with pre-punched holes every 6 inches on center and is used in conjunction with Kingspan Membrane Fasteners to secure approved Kingspan membranes to steel, wood, and concrete decks.



Manufactured in the U.S.A.

Kingspan Metal Batten Strip is manufactured in the U.S.A. with globally sourced materials.



Features & Benefits

- FM assemblies available for installing approved Kingspan membrane.
- Solid design featuring 18-gauge steel and pre-punched, counter sunk holes spaced 6 inches o.c.
- Packaging: 500 linear feet per tube with 50 – 1-in. x 10-ft. (3.05 m) long pieces per tube.

Codes & Approvals



Application

- Prior to job start, a pullout test should be performed to determine sufficient pullout values. Contact Kingspan Roofing + Waterproofing for assistance in setting this up.
- The Kingspan Metal Batten Strip can be used to mechanically attach Kingspan membranes to steel, wood, and concrete decks via intermediate rows of fastening where prescribed enhancements are required.

- For membrane installation, use a screw gun with an appropriate Kingspan Membrane Fastener through the pre-punched, counter sunk holes of the Kingspan Metal Batten Strip until fully secured.
- Use of a reinforced cover strip is required in conjunction with Kingspan Metal Batten Strips to ensure watertightness of mid roll rows.

Safety Precautions

- Use proper equipment and assistance when moving, lifting, handling, or transporting Kingspan Metal Batten Strip to avoid personal injury as well as damage to the materials. Note: Kingspan Metal Batten Strips ship in tubes that weight 80 lbs. (36.29 kg).
- Protective eyewear must be worn during installation of Kingspan Metal Batten Strips.
- Reference the Kingspan product Safety Data Sheet for additional safety information.

Storage

- Store Kingspan Metal Batten Strips in a controlled, dry environment, away from objects that could cause physical damage to product or packaging.

Typical Properties & Product Information

SKU	Count	Linear Feet per Tube	Tube Weight Lbs. (kg)
600000001582	50 – 1-in. x 10-ft. pieces per tube	500 ft.	80 lbs. (36.29 kg)

Kingspan Roofing + Waterproofing, Inc.
4115 N. Perkins Road | Stillwater, OK 74075

T: +1 (800) 260-0365 E: support.krw@kingspan.com
www.kingspanroofing.com

Care has been taken to ensure that the contents of this publication are accurate, but Kingspan Limited and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Kingspan Limited and its subsidiaries accept no liability in respect thereof.

For the product offering in other markets please contact your local sales representative.

© Kingspan and the Lion Device are Registered Trademarks of the Kingspan Group plc in the UK, Ireland and other countries. All Rights reserved. Registered in the U.S.

