

Product Description

The Kingspan Zamac Nailing Fasteners are 1-¼" long nail-driving anchors used to attach Kingspan Termination Bar to seal membrane and flashing terminations into approved substrates.



Features & Benefits

- **Corrosion Resistant:** nailing anchor approved for attachment into concrete, block, stone, brick, or other approved substrates in conjunction with the Kingspan Termination Bar.
- **Provides watertight protection** when installed with Kingspan Termination Bar, according to Kingspan specification and detail.

Application for Termination System (including Kingspan Zamac Nailing Fasteners)

- Prior to application, clean all surfaces to receive the Kingspan Termination Bar and Water Block Sealant with the Kingspan TPO Membrane Cleaner.
- Apply a continuous bead of Kingspan Water Block Sealant behind the top of the Kingspan Termination Bar.
- When installing the Kingspan Termination Bar, make sure all corners of cut bar are rounded. Also, maintain ¼" separation between adjoining termination bars.
- Install Kingspan Zamac Nailing Fasteners perpendicular to the wall and through the pre-punched holes in the Kingspan Termination Bar. Be sure to maintain constant compression.

- Install the flat side of the termination bar against the flashed wall, creating a caulk lip at the top edge and bottom edge between the termination bar and the wall for the sealant application.
- Apply Kingspan General Purpose Sealant into both the top and bottom caulk lips between the termination bar and the membrane wall to seal off the termination system.

Safety Precautions

- Use proper equipment and assistance when moving, lifting, handling, or transporting to avoid personal injury as well as to avoid damaging the material.
- Reference the Kingspan product Safety Data Sheet for additional safety information.

Storage

- Keep all Kingspan membrane terminating materials clean and dry prior to installation.

Typical Properties & Packaging Information

Ordering SKU	Material	Count	Weight
600000001032	Zamac Alloy	1,000 fasteners	21 lbs. (9.5 kg)

Kingspan Roofing + Waterproofing, Inc.
4115 N. Perkins Road | Stillwater, OK 74075

T: +1 (800) 260-0365 E: support.krw@kingspan.com
www.kingspanroofing.com

Care has been taken to ensure that the contents of this publication are accurate, but Kingspan Limited and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Kingspan Limited and its subsidiaries accept no liability in respect thereof.

For the product offering in other markets please contact your local sales representative.

© Kingspan and the Lion Device are Registered Trademarks of the Kingspan Group plc in the UK, Ireland and other countries. All Rights reserved. Registered in the U.S.

